



## AXI-IPC-B60S2360

- \* 2 Mega Pixels Full HD Network IR Bullet Camera
- \* 1/2.5" Image Sensor
- \* 3 Mega Pixel 8mm M12 Lens
- \* Germany Osram Infra Red 5µm X 48 Pcs
- \* Built-in POE 802.3af
- \* DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC
- \* Advanced H.264 High profile compression
- \* Support Several Servers, CMS, IP Address, DDNS, FTP, SMTP
- \* ONVIF 2.3
- \* Support Single, Dual streams, Low streams and high resolution image
- \* IP 66 Class (High Pressure Water Jets from any Direction)



### Specification

<b>Model</b>	<b>AXI-IPC-B60S2360</b>
Image Sensor	1/2.5" Image Sensor
Mega pixel	2 Mega pixel
Effective Pixels	1920(H) X 1080(V)
Lens	3 Mega Pixel 8mm M12 Lens with Angle of view 85°
IR LED	Germany Osram Infra Red 5µm X 48 Pc
IR Range Distance	60 Meters Range
IP Class	IP66
Minimum Illumination	Color: 0.02 Lux/F1.4, B/W: 0.01Lux/F1.4; 0Lux/F1.2(IR on)
Electronic Shutter Speed	Auto/Manual, 1/3~1/10000s
Back Light Comp.	BLC / HLC / DWDR
PoE	Built-in PoE 802.3af
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Video Processing	H.264 Video Code, Support dual-stream, 32k-8m adjustable, 1-30/s frame rate adjustable
Video Resolution	1080P(1920y1080) / 720P(1280y720) / D1(704y576/704y480) / CIF(352y288/352y240)
Main Stream	1080P/720P(1 ~ 25/30fps)
Sub Stream	D1/CIF(1 ~ 25/30fps)
Standard protocol	Onvif 2.3
Network Port	1 RJ45 Ethernet interface, 10/100M adaptation
Network Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
Delay	Within the LAN 0.3S
Frame Rate	50Hz: 25fps(1920 y 1080), 25fps (1280 y 960), 25fps (1280 y 720) 60Hz: 30fps(1920 x 1080), 30fps (1280 x 960), 30fps (1280 x 720)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 24576Kbps
Video Compression	H.264/JPEG,support AVI format.
Operation Function	Support Web setting, OSD, real-time video transmission, motive detection and IO alarm; support MJPEG capture, CMS platform
Mobile Phone Monitor	iPhone, iPad, Android
Power Supply	DC12V(AC24 optional), PoE(802.3af)
Working Temperature	.-20°C~60°C
Humidity	0%-90% RH,Without Condensation
Color/Material	White / Alloy Metal
Dimensions(W×H×D)	130mm X 80mm X 130mm
Weight	650 Gram (Approximately)

Design & Specifications are subject to change without Prior notice

Nothing Can Escape from the Altron Eye

