



AX-NVR-5508-5P

- * 8 Channel Enterprises Network Video Recorder
- * Support 8 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP Input
- * Up to 8 Mega pixels resolution recording
- * Support H.265+ / H.264 Compression Video Formats
- * Accurate retrieval, instant playback
- * Support HDD hot swap with RAID1, 5 Storage Scheme Configurable
- * 1 SATA HDD Bay with up to 8TB for each HDD
- * Support various VCA detection alarm and VCA search
- * Support for P2P, UPnP, NTP, DHCP, PPPoE
- * Support for mobile client access



Specification

Model	AX-NVR-5508-5P
System	
Compression	Standard H.265+
Main Processing Chip	ARM Cortex A17
OS	Embedded Linux
Video	
Network Access Bandwidth	256Mbps
Input Resolution	8MP \ 5MP \ 4MP \ 3MP \ 1080P \ 960P \ 720P Real Time
Network Access	8 CH IPC input
Output	HDMI×1:3840×2160/1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768
Audio	
Input	2 CH IPC audio input
2-way Audio	RCA×1
Local Output	RCA×1
Record	
Resolution	8MP \ 5MP \ 4MP \ 3MP \ 1080P \ 960P \ 720P
Frame Rate	25FPS / 30FPS (PAL/NTSC)
Bite Stream	32Kbps-12Mbps
Image Quality	5 Level
Playback	
Simultaneous Playback	Max 4 CH
Network	
Interface	RJ45 10/100/1000 Mbps x 1; RJ45×16 (PoE Port)
Network Protocol	TCP/IP \ PPPoE \ DHCP \ DNS \ DDNS \ UPnP \ NTP \ SMTP \ ONVIF \ GB28181
Storage	
HDD	1 Nos. Of SATA
Max Capacity for HDD	8 TB
Backup	
USB Backup	Yes
eSata Backup	No
Interface	
Alarm In	1
Alarm Output	1
Communication	RS485×2, connect to PTZ and keyboard
Remote	Optional
USB	USB2.0×1 (Front panel), USB3.0×1 (Rear panel)
Others	
Case	1.2U
Dimensions(mm)	240×290×60(W×D×H)
Power Supply	ATX
Consumption	? 30W (without HDD)
Work Environment	-10 □ 50 □ 10% □ 90% humidity

Design & Specifications are subject to change without Prior notice

Nothing Can Escape from the Altronx Eye

